

- ^ Output resolution: up to 4K if HDMI only; up to 1080p if HDMI & VGA dual output
- ^ BYOD and native protocols support
- ^ 4 contents shared simultaneous on screen
- ^ Wireless collaboration functions
- ^ Up to 20 simultaneous connections

Compatible OS	Windows 10+ macOS 10.14+ Chrome OS 84.0.4147.110+	Android 8.0+ (10.0+ with audio mirror) iOS 14+
Support protocol	BeamOp, AirPlay, Google Cast, Browser Sharing	
Video output	HDMI / VGA	
Output resolution	HDMI only: 4K@30Hz; HDMI + VGA dual output: 1080p@60Hz	
Audio output	HDMI & Audio Jack 3.5mm	
Wi-Fi Band	Switchable dual band 2.4GHz / 5GHz (DFS channels not supported)	
Wireless transmission protocol	IEEE 802.11ac	
Encryption protocol	AP mode: WPA2-PSK Station mode: WEP, WPA, WPA2, 802.1x EAP	
Ethernet	10/100/1000 Mbps RJ-45 LAN (support PoE)	
Interface	1 x HDMI, 1x VGA 1 x USB 2.0 Host Type-A 1 x USB 3.0 Host Type-A 1 x USB 3.0 Host Type-C	1 x 3.5mm Audio Jack 1 x 10/100/1000 Ethernet LAN 1 x Power Jack
Power supply	12V 2A	
Net weight	500g	
Dimension	170mm x 104.4mm x 30.5mm (HxWxD)	
Temperature	Operating: 0° – 40° C (32° – 104° F) Storage: -10° – 70° C (14° – 158° F)	
Humidity	Operating: 20 – 80% non-condensing Storage: 10 – 90% non-condensing	
Certificate	FCC, CE, NCC, BSMI	
Warranty	3 years	

- ^ Output resolution: up to 4K if HDMI only; up to 1080p if HDMI & VGA dual output
- ^ BYOD and native protocols support
- ^ 2 contents shared simultaneous on screen
- ^ Up to 8 simultaneous connections

Compatible OS	Windows 10+ macOS 10.14+ Chrome OS 84.0.4147.110+	Android 8.0+ (10.0+ with audio mirror) iOS 14+
Support protocol	BeamOp, AirPlay, Google Cast, Browser Sharing	
Video output	HDMI / VGA	
Output resolution	HDMI only: 4K@30Hz; HDMI + VGA dual output: 1080p@60Hz	
Audio output	HDMI & Audio Jack 3.5mm	
Wi-Fi Band	Switchable dual band 2.4GHZ / 5GHz (DFS channels not supported)	
Wireless transmission protocol	IEEE 802.11ac	
Encryption protocol	AP mode: WPA2-PSK Station mode: WEP, WPA, WPA2, 802.1x EAP	
Ethernet	10/100/1000 Mbps RJ-45 LAN	
Interface	1 x HDMI, 1x VGA 1 x USB 2.0 Host Type-A 1 x USB 3.0 Host Type-A 1 x USB 3.0 Host Type-C	1 x 3.5mm Audio Jack 1 x 10/100/1000 Ethernet LAN 1 x Power Jack
Power supply	12V 2A	
Net weight	500g	
Dimension	170mm x 104.4mm x 30.5mm (HxWxD)	
Temperature	Operating: 0° – 40° C (32° – 104° F) Storage: -10° – 70° C (14° – 158° F)	
Humidity	Operating: 20 – 80% non-condensing Storage: 10 – 90% non-condensing	
Certificate	FCC, CE, NCC, BSMI	
Warranty	3 years	