

# ClickShare Hub Pro

Premium modular video conferencing room system for enhanced hybrid meetings



- **Wireless presentation: 4K content sharing with 2 next-gen ClickShare Buttons with USB-C DisplayPort™**
- **Dual display support**
- **Secure by design, cloud-managed, and built on the Microsoft Device Ecosystem platform (MDEP)**
- **Sustainable product with Barco Eco label A+**

ClickShare Hub Pro is a premium modular, wireless video conferencing system for enhanced hybrid meetings. Featuring two next-gen ClickShare Buttons (with Wi-Fi 6E and USB-C DisplayPort™), it ensures meeting participants enjoy secure, 4K wireless content sharing. With dual display support, it guarantees highly visual and engaging meetings.

For IT managers and integrators, ClickShare Hub Pro offers a customizable solution for all room types, enterprise-grade security and compliance.

Expected to be available end of 2025.

## Product specifications

## CLICKSHARE HUB PRO

### General specifications

|                                |                                                                                                                                                                                                                                                                     |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating system               | Windows 10 or higher macOS 14 (Sonoma) and 15 (Sequoia)                                                                                                                                                                                                             |
| System requirements            | Minimum: Intel Core i3 or AMD Ryzen 5, 8GB RAM, Windows 10 20H2; Intel Core i3 or Apple Silicon M1, 8GB RAM, macOS 11 Big Sur<br>Recommended: Intel Core i5/Ultra 5 or AMD Ryzen 7, 8GB RAM, Windows 11 latest build; Apple Silicon M3, 8GB RAM, macOS latest build |
| Video outputs                  | HDMI-1: UW5K WUHD (5120*2160) @30Hz HDMI 2.0 HDMI-2: 4K UHD (3840*2160) @30Hz HDMI 2.0 eDP (Control Panel): HD (1280*800) @60Hz DP 1.4                                                                                                                              |
| Video inputs                   | 4K UHD (3840*2160) @30Hz HDMI 2.0                                                                                                                                                                                                                                   |
| Audio output                   | USB-A 2.0/3.0 USB-C 2.0/3.0 HDMI 2.0                                                                                                                                                                                                                                |
| ClickShare Buttons             | 2 * ClickShare Button 5th Generation                                                                                                                                                                                                                                |
| ClickShare App                 | Desktop                                                                                                                                                                                                                                                             |
| Noise Level                    | Maximum 25 dBA @ 30°C                                                                                                                                                                                                                                               |
| Wireless transmission protocol | IEEE 802.11 a/b/g/n/ac/ax/be and IEEE 802.15.1 BT 5.3                                                                                                                                                                                                               |
| Reach                          | Max. 30m (100ft) between ClickShare Button and ClickShare Base Unit                                                                                                                                                                                                 |
| Frequency band                 | 2.4GHz, 5GHz and 6GHz DBS/HBS (DFS channels supported in select number of countries)                                                                                                                                                                                |
| Connections                    | Back: 1x Ethernet LAN 1Gbit 1x USB-C Power delivery 3.1 EPR (for power adapter) 2x HDMI 2.0 output 2x USB-C 2.0/3.0 1x USB-A 2.0/3.0 1x USB-C 2.0/3.0 Device + USB-C DisplayPort™ output 1x USB-C 2.0 + USB-C DisplayPort™ output<br>Front: 1x USB-C 2.0/3.0        |
| Temperature range              | Operating: 0°C + 40°C (+32°F to +104°F) Max 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)                                                                                                                                                           |
| Humidity                       | Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing                                                                                                                                                           |
| Anti-theft system              | Kensington lock                                                                                                                                                                                                                                                     |
| Certifications                 | FCC/CE                                                                                                                                                                                                                                                              |
| Network connection             | LAN                                                                                                                                                                                                                                                                 |
| Management and reporting       | Yes, XMS Cloud                                                                                                                                                                                                                                                      |
| Warranty                       | 3 years standard                                                                                                                                                                                                                                                    |
| Dimensions (HxWxD)             | 37 * 180 * 180 (mm)                                                                                                                                                                                                                                                 |
| Power consumption              | Operational: 160W (max) Standby:                                                                                                                                                                                                                                    |
| Power supply                   | External USB-C charger 100W (PD3.0 SPR), 180W (PD3.1 EPR)                                                                                                                                                                                                           |
| Weight                         | 720gr                                                                                                                                                                                                                                                               |

Last updated: 26 Sep 2025

© 2025 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.